



Step by step tutorial: of Hyundai Crystal 10 Rear camera

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



Opening tool
Smartphone, tablet

2,19 €



Pinza antiestática
ESD redondeada

3,06 €



Anti-static tweezers
tips VETUS ESD-249

4,74 €



Special SAT 0.70mm
PET pick, high friction
and resistance

1,25 €



Smartphones and PC
repair tool case

35,92 €

Step 1 - Hyundai Crystal 10

Characteristics:

Dimensions: 26 x 16 x 1cm approx.

Weight: N / D

Display: 10 " (25.6 cm) IPS, 1920x1200 pixels.

Processor: Intel® Atom Z3735F.

Memory: Internal 16GB, 2GB RAM, SD up to 64GB.

Front camera : 2Mpx.

Rear camera : 5 Mpx.

Battery: 7100mAh

Operating system: Android 4.4.

We will start by removing the microSD card from one side of the tablet. To do this, we will press the card slightly so that it is automatically ejected.





Step 2 - Side trim screws

Before removing the back cover, we will remove the screws from the metal side trims.



Step 3 - Back case

With the help of an opening tool, we will unhook the notches that hold the back housing to the frame.





Step 4 - Rear camera

It only remains to disconnect the camera from the base plate and detach it from the frame to be able to remove it.



