




NadieMeLlamaGallina.com

Porque Yo Lo Reparo

Step by step tutorial: of Xiaomi Mi5 Front button

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



Flex with white home button for Xiaomi Mi5

2,24 €



SIM card removal tool for all brands

1,61 €



Screwdriver with 8 heads Peng Fa 7339A

6,96 €



Opening tool Smartphone, tablet

2,19 €



Pinza antiestática ESD redondeada

3,06 €



Stripper gun, hot air welder for repairs

15,59 €



Special SAT 0.70mm PET pick, high friction and resistance

1,25 €



Suction cup for disassembling and repairing

0,51 €

Step 1 - Tray yes

First we extract the sim tray.





Step 2 - Back case

With the help of a pick and a suction cup we remove the back cover.



Step 3 - Intermediate housing

Remove the 9 Phillips screws (PH # 00) that hold the intermediate housing and remove it.



Step 4 - Antenna module with loudspeaker

Remove the 7 Phillips screws and remove the antenna module with loudspeaker.





Step 5 - Frontal camera

We removed the front camera.



Step 6 - Components

We disconnect all the components that are connected to the motherboard.





Step 7 - Motherboard

Remove the Phillips screws (PH # 00) that hold the plate, and remove it.





Step 8 - Battery

We extract the battery.



Step 9 - Interconnection Flex with auxiliary plate

We disconnect the components that are connected to the auxiliary plate, take it off and remove it.





Step 10 - Fullscreen

We apply heat to the edges of the screen to detach it more easily, disconnect the flex from the screen and remove it.





Step 11 - Front button

And finally, we can remove the button that we are going to replace.

