



NadieMeLlamaGallina.com

Porque Yo Lo Reparo

Step by step tutorial: of Sony Xperia L1 Rear camera

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



13 Mpx Rear Camera
for Sony Xperia L1,
G3311

3,48 €



Head made of
synthetic carbon steel
with titanium handle

18,63 €



Opening tool
Smartphone, tablet

2,19 €



JM-8142 Screwdriver
Kit with 24 Heads

11,24 €



Special SAT 0.75mm
high friction PVC pick

1,07 €



Touch ESD glove, for
antistatic protection,
size M

4,16 €



Antistatic and ESD
tactile glove, size S

5,30 €

Step 1 - The NFC antenna housing

To begin we must remove the back cover with NFC antenna, for this we will use a plastic pick and we will take off all the edges of the casing.





Step 2 - Upper housing and antenna module with speaker

We extract the fourteen Torx screws (T5) and unhook the upper housing and the antenna module with loudspeaker.





Step 3 - Side frames

Using a flat tool, unhook both side frames.





Step 4 - Motherboard

We disconnect all the components that are connected to the motherboard, remove the tray from the sim card, and remove the motherboard.





Step 5 - Rear camera

Finally, we just have to disconnect the rear camera that we are going to replace.

