



Step by step tutorial: of Sony Xperia Z2 Antenna

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



Antenna Sony Xperia Z2, L50W, D6502, D6503, D6543

0,95 €



Screwdriver 15 in 1, Mobiles and Tablets BK-315

5,48 €



Opening tool Smartphone, tablet

2,19 €



ESD-12 precision antistatic tweezers with fine tip

2,17 €



Stripper gun, hot air welder for repairs

15,59 €



Special SAT 0.75mm high friction PVC pick

1,07 €

Step 1 - SIM and microSD cards

Before starting make sure that the mobile is off.

Remove the SIM and micro SD cards.





Step 2 - Opening

To be resistant to water, the Z2 comes completely sealed. To open the back cover we apply heat to soften the glue. Use the hot air gun or HOT GLASS to heat the back cover.

Once opened this smartphone will lose the water resistance.



Step 3 - Back cover

Insert the tip of the tine behind the back cover and traverse the contour to detach the adhesive.



Step 4

Separate the back cover, this contains the NFC antenna.



Step 5 - Antenna

Remove the Phillips screw.

Disconnect the coaxial cable.





Step 6

Finally, take off the antenna.



