



NadieMeLlamaGallina.com

Porque Yo Lo Reparo

Step by step tutorial: of Motorola Moto Z2 Play Card reader

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



Gray SIM/SD reader and flex for Motorola Moto Z2 Play XT1709, XT1710

3,96 €



Screwdriver with 28 tips JK 6032-A

5,51 €



Heat-opening thermal mat, CPB320

69,61 €



Professional disassembly spatula for mobile phones and smartphones

2,71 €



Opening tool Smartphone, tablet

2,19 €



Pinza antiestática ESD redondeada

3,06 €



Special SAT 0.70mm PET pick, high friction and resistance

1,25 €



Suction cup to separate screens in general

5,25 €



Antistatic and ESD tactile glove, size S

5,30 €

Step 1 - Take off screen

We start by removing the screen. For this we heat it to about 60°C for about a minute.

With the hot screen, we slide a flat tool around the contour to take it off. We will try not to bend it much and we will not approach the display to avoid damaging it.





Step 2 - Remove screen

Once detached, we will open it as a book to disconnect the flex from the home button and the screen button.



Step 3 - Remove intermediate housing

Remove the fifteen screws that hold the upper and lower housings and disengage them. Then we remove the SIM / SD tray.





Step 4 - Removing the motherboard

In this step, we disconnect the battery and remove the three T3 Torx screws that hold the plate. We will take off the rear camera and the flex of the SIM / SD card reader to finally disengage it.





Step 5 - Card reader

All that remains is to disconnect the reader from the motherboard.

